



HANDMADE IN THE USA

PILOT-HD

Heavy Duty Construction,
Highest Power Motors and
Handmade in America
Why Look Anywhere Else?

DRAIN SAVER
KEEPS DEBRIS OUT
OF DRAINS

36 VOLT SYSTEM
RUNS FOR FULL
SHIFT

2 TANK SYSTEM
EASILY DRAIN
RECOVERY TANK

ROLLERS (6" TALL)
PROTECTS WALLS
AND KICK PLATES

HD FRONT DRIVE
CLIMB RAMPS

DISK OR CYLINDRICAL
SCRUB DECK

SMALL FOOTPRINT!
CLOSE CLEANING!



FACTORYCAT
INDUSTRIAL CLEANING EQUIPMENT



Scan This QR
Code With
Your Phone
For More
Information

www.factorycat.com
1(800)634-4060
(+001)262-681-3583



Series Scrubber Specifications

FC-PILOT-HD

AUTHORIZED DISTRIBUTOR

BODY CONSTRUCTION / DIMENSIONS

Tank Material:	Poly 3/8" (10 mm)
Chassis Construction:	1/8" Steel (3mm) Powder Coated Steel
Front Wheel (Diameter x Width):	8" x 3" (20 x 8 cm) - Non-Marking Solid Grey
Rear Wheels (Diameter x Width):	(2x) 12" x 3" ((2x) 31 x 8 cm) - Solid Black
Size (L x W x H):	48" x 24" x 55" (122 x 61 x 140 cm)
Weight (w/o Batteries):	525 - 575 lbs (238 - 261 kg)
Weight (w/ 245 ah Batteries):	825 - 875 lbs (374 - 397 kg)

BRUSH / PAD SYSTEM

Disk Dimensions:	26" - (2x) 13" Diameter (66 - [2x] 33 cm) 28" - (2x) 14" Diameter (71 - [2x] 36 cm)
Disk Motor:	26" & 28" - (2x) 0.75 hp / 300 rpm ((2x) 559 watts)
Disk Brush Speed:	300 rpm
Cylindrical Dimensions:	25" - (2x) 6" x 23" (64 - [2x] 15 x 58 cm) 6" Diameter Brush
Cylindrical Motor:	(2x) 0.75 hp / 350 rpm ((2x) 559 watts)
Cylindrical Brush Speed:	750 rpm
Actuator Rating:	500 lbs (227 kg)
Brush Pressure Settings:	(5) with Auto Adjust
Brush Down Pressure:	Up to 150 lbs (68 kg)

POWER SYSTEM

System Voltage:	36 VDC
Standard Battery:	175 ah WET
Optional Battery:	225 ah WET / 215 ah AGM
Run Time:	Up to 4.0 Hours**
**Run times are based on continuous scrubbing run times.	
Charger:	120VAC / 60 Hz Input - 36VDC / 25 amp Output

DRIVE SYSTEM:

Power:	0.75hp - All Gear / Sealed (559 watts)
Forward Speed:	0 - 320 ft/min (4 mph) 0 - 98 m/min (6 km/h)
Reverse Speed:	0 - 230 ft/min (3 mph) 0 - 70 m/min (5 km/h)

SOLUTION / RECOVERY SYSTEMS:

Solution Tank Capacity:	22 Gallons (83 liters) - w/ Graduated Site Tube
Solution Flow / Filter:	0 - 1.0 GPM / Stainless Inline (0 - 4 LPM)
Recovery Tank Capacity:	23 Gallons (87 liters) - 2" diameter Drain Hose
Demisting Chamber:	1.25 Gallons (5 liters)
Drain Saver:	30 cubic inches (492 cubic cm)
Vacuum Power:	1.0 hp / 2 Stage (740 watts)
Vacuum Specs (Water Lift / Airflow):	68" / 72 cfm (173 cm / 2 cm/m)
Squeegee:	36" Curved w/ 4-sided Rear Blade & Quick Change Latch

GENERAL:

Cleaning Width:	26" & 28" - Disk (66 & 71 cm) 25" - Cylindrical (64 cm)
Decibels:	67 dB
Productivity - Theoretical:	Up to 40,000 sqft (3,716 sqm)***
***Productivity is based off of ISSA 2010 Cleaning Times	
Productivity - Practical:	Up to 18,519 sqft (1,721 sqm)***
***Productivity is based off of ISSA 2010 Cleaning Times	
Seat with Switch Included	

FACTORY CAT

www.factorycat.com

Phone: (800) 634-4060

International: (+001) 262-681-3583

© RPS Corporation 2016

All Rights Reserved

As our policy is one of constant improvement, all specifications are subject to change without notice.

(10/16) FC-PILOT-HD-SALESSHEET